




VITI TRUCIOLARI CHIPBOARD SCREWS

C15 CEMENTATE - CARBON STEEL C15 HARDENED
TESTA SVASATA – COUNTERSUNK HEAD
IMPRONTA CROCE POZI – POZI CROSS RECESS

COD 21221

UNI
DIN 7505 - A
ISO



		2,5	3,0	3,5	4,0	4,5	5,0	6,0
A	min	4,70	5,50	6,40	7,40	8,20	9,20	10,90
	max	5,00	5,80	6,70	7,70	8,50	9,50	11,40
D	min	2,35	2,75	3,35	3,80	4,30	4,75	5,75
	max	2,50	3,05	3,55	4,10	4,60	5,10	6,20
pz		1	1	2	2	2	2	3

Lunghezza / Lenght mm.	Diametro / Diameter mm. (*)						
	2,5	3,0	3,5	4,0	4,5	5,0	6,0
10							
12							
14							
15							
16							
18							
20							
22							
25							
30							
35							
40							
45							
50 / 40							
50 / 50							
55							
60 / 40							
60 / 50							
60 / 60							
65							
70 / 50							
70 / 60							
70 / 70							
75 / 60							





VITI TRUCIOLARI CHIPBOARD SCREWS

C15 CEMENTATE - CARBON STEEL C15 HARDENED
TESTA SVASATA – COUNTERSUNK HEAD
IMPRONTA CROCE POZI – POZI CROSS RECESS

COD 21221

UNI
DIN 7505 - A
ISO



		2,5	3,0	3,5	4,0	4,5	5,0	6,0
A	min	4,70	5,50	6,40	7,40	8,20	9,20	10,90
	max	5,00	5,80	6,70	7,70	8,50	9,50	11,40
D	min	2,35	2,75	3,35	3,80	4,30	4,75	5,75
	max	2,50	3,05	3,55	4,10	4,60	5,10	6,20
pz		1	1	2	2	2	2	3

Lunghezza / Lenght mm.	Diametro / Diameter mm. (*)						
	2,5	3,0	3,5	4,0	4,5	5,0	6,0
80 / 50							
80 / 60							
80 / 80							
83 / 60							
85 / 60							
90 / 60							
90 / 90							
100 / 60							
100 / 100							
110 / 60							
120 / 60							
120 / 120							
130 / 60							
140 / 60							
150 / 60							
160 / 60							
180 / 60							
200 / 60							

PRODUZIONE STANDARD